



## HiPath Cordless Office for the HiPath 500 and HiPath 3000 Series

HiPath Cordless Office is the integrated cordless solution in the HiPath 500 and HiPath 3000 series for cordless communication with convenient user and system features.

Providing employees with cordless phones permits direct communication regardless of location, presenting the perfect solution for immediate availability and quick decision-making and creating both administrative and economic advantages.

**SIEMENS**

Global network of innovation

The HiPath Cordless Office system architecture is highly flexible as regards

- number of subscribers,
- subscriber density,
- coverage,
- extensibility and the provision of new features with up-to-date telephones.

The system uses the worldwide digital radio transmission standard DECT (Digital Enhanced Cordless Telecommunication), operating in a protected frequency band, and it supports an open interface according to the GAP (Generic Access Profile) standard.

HiPath Cordless Office also lays the foundation for high mobility and constant availability in companies across different sites and on company grounds extending over a wide area.

HiPath Cordless Office thus offers a high degree of investment protection with future-oriented functions and features based on the modern DECT and GAP standards.

## System Features

### Feature handsets

A high degree of flexibility and mobility makes the "Gigaset S1 professional, SL1 professional and Gigaset active M" handsets firm favorites amongst cordless telephones. They offer excellent digital speech quality, a high degree of immunity to eavesdropping and a long range (up to 50 meters indoors and up to 300 meters outdoors).

Not only are investment and operating costs low; the handsets also feature easy user prompting and a 4-line display with menu selection keys.

Another plus is that access to the entire cordless system is protected: "third-party" cordless phone users are prevented from gaining unauthorized access as the handsets are logged on to the system centrally.

The HiPath Cordless Office feature handsets allow users to conduct phone calls throughout the radio-provisioned area. With the feature handsets it is possible to use the HiPath 500 and HiPath 3000 communication system's features while moving around the grounds (toggle, consultation, conference).

### Base stations

The base stations form the radio cells and conduct communication with the cordless terminals (feature handsets). They are connected with 1 to 3 system-specific  $U_{PO/E}$  interfaces to the radio switch or with 1  $U_{PO/E}$  interface directly to the system control. The type of connection depends on the system variant. This allows up to 12 calls (when 3  $U_{PO/E}$  are connected) to be conducted simultaneously via one base station.

The precise location of the base station must be determined using radio illumination measurements and project planning to ensure the radio network is optimally sited for covering the building or grounds. Specialized antennas can be used for increased radio coverage. The base stations can be encased to protect them from the weather.

### System connection

Depending on the system capacity stage, handsets are connected to the system either via a radio switch or directly to the system control. User data administration for the entire cordless system is performed directly by the system software, giving the advantage of simple system management.

A different number of base stations and handsets is supported (see Technical data), again depending on the HiPath system capacity stage.

Depending on its configuration, each  $U_{PO/E}$  interface can provide 2 or 4 voice channels. The HiPath Cordless system can be extended from one directly connected base station with two simultaneous calls to 64 base stations connected via four radio switches with 250 simultaneous calls.

A maximum of 7 base stations and 28 connections are possible in the case of a direct connection.

(For larger-scale upgrades, the base stations and phones can be migrated to the HiPath Cordless Enterprise system of HiPath 4000.)

## Multi-cell technology

The radio coverage required in the building or on company grounds is achieved by means of multi-cell technology. The radio cells of the base stations installed in the company overlap so that calls throughout the cordless system domain can be set up and conducted smoothly while users are moving around (roaming and handover).

## System networking

With networked systems, accessibility across system boundaries is also provided by the system with additional functions. The accessibility range can be further extended with the cross-system roaming function.

### Cross-system roaming

In a system network with up to 16 systems, the cross-system roaming function supports unlimited accessibility on the same internal phone number. Connections between the systems using the Siemens-specific CorNet N protocol are a requirement for this. Following change-over to another location, the handset logs on here using its home identification and directory number. This information is transferred over the digital connection to the home system so it knows where the user is located and can automatically forward incoming calls over the system connection.

# Gigaset Handsets

## Gigaset S1 professional

### Features

- Handset lock by means of four-digit PIN
- Handset can be charged in disabled mode (PIN set)
- Illuminated hands-free key
- Illuminated MWI key
- Telephone book
- Voice dialing for up to 29 entries
- Display
- Conducting calls
- Ten tones/melodies can be set for internal and external calls
- Three-level audio volume adjustment
- Visual call signaling
- Menu prompting in 19 languages
- DPS (DECT Position System)

### Handset operating times

Standby up to 170 hours  
Talk time up to 13 hours

### Dimensions (L x W x D in mm)

147 x 54 x 26

Weight including batteries 130g

### Gigaset S1 professional charger

#### Charging time for NiCd batteries

8 to 9 hours

#### Power supply

220/230 V AC plug-in power supply unit  
110 V AC plug-in power supply unit

## Gigaset active M industrial handset

### Features similar to Gigaset S1 professional

- Shock and shatter-proof casing
- Dust proof
- Water splash and spray protection
- Enhanced interference suppression
- Illuminated keypad
- Keypad suitable for use with protective gloves
- Acoustics optimized to suit loud environments
- Headset connection
- Alarm button
- Vibration alarm
- Speakerphone mode
- Robust belt clip
- Recharging facility with external charging device

Weight incl. batteries approx. 141g

## Gigaset SL1 professional

### Features similar to Gigaset S1 professional

- Vibration alarm
- Headset connection
- PC interface for telephone book transfer (accessories from the C/S55 mobile series can be used)
- Locating capabilities
- DPS (DECT Position System)

### Handset operating times

Standby up to 250 hours  
Talk time up to 15 hours

### Dimensions (L x W x D in mm)

114 x 47 x 22

Weight incl. batteries approx. 100g

### Gigaset SL1 professional charger

#### Charging time for NiCd batteries

8 to 9 hours

#### Power supply

220/230 V AC plug-in power supply unit  
110 V AC plug-in power supply unit



# Technical Data

## System data

Radio interface standard: DECT (ETS 300 175), GAP (ETS 300 444)

Frequency band:  
1,880 MHz to 1,900 MHz  
1,910 MHz to 1,930 MHz

Number of carriers: 10 (switchable)

12 full duplex channels

Voice encoding: 32 kbps ADPCM

CE Standard (Safety)

## System configuration

Integrated/can be integrated in

- **HiPath 520**  
Direct connection: Maximum of 1 BS3/S base station with up to 2 simultaneous call connections and up to 8 handsets
- **HiPath 540**  
Direct connection: Maximum of 3 BS3/1 base stations with 2 simultaneous call connections and up to 8 handsets
- **HiPath 580**  
Direct connection: Maximum of 3 BS3/1 base stations with 2 simultaneous calls and up to 16 handsets
- **HiPath 3300/3350**  
Direct connection: Maximum of 3 BS3/1 base stations with every 4 call connections and up to 16 handsets or 1 BS3/S with 2 call connections and up to 8 handsets
- **HiPath 3500/3550**  
Direct connection: Maximum of 7 BS3/1 base stations with every 4 call connections and up to 32 handsets or 1 BS3/S with 2 call connections and up to 8 handsets

- **HiPath 3700/3750**  
Up to 4 radio switches per 16 interfaces  
Maximum of 4 BS3/1 or BS3/3 base stations (up to 3 interfaces) with 4 to 12 simultaneous call connections and up to 250 handsets  
(released on a country-specific basis)

## Radio switch

for connecting to the DECT base station

- Number of line interfaces: 16
- Type: 2  $U_{P0/E}$  wires for standard telephone line or separate STP-LAN cabling
- Number of channels per line interface: 4 32 Kbps voice channels
- Coverage:
  - up to 500m for direct connection
  - Remaining HiPath 3000 series up to 1000m

## DECT base stations

EMC according to EN 55024/EN 55022/EN 301406

Radio interface according to EN 301406 (1TBR6)

### Line interface

- Type: 2  $U_{P0/E}$  wires
- Number of channels: 2/4 32 Kbps B channels
- Number of line interfaces: 1 for BS3/1 and BS3/S; 3 for BS3/3
- Power supply voltage: 42V to 54V  
( $U_{xP0/E}$  nominal voltage = 48V)

### BS3/1 or BS3/S casing (1x $U_{P0/E}$ )

- Dimensions (L x W x D in mm): 181 x 139 x 69
- Weight: 266g
- Power draw: max. 1.7W



### BS3/3 casing (3x $U_{P0/E}$ )

- Dimensions (L x W x D in mm): 202 x 172 x 43  
(+ 44mm for antennas)
- Weight: 474g
- Power draw: max. 3.2W



Indoor temperature range:  
in accordance with IEC721-3-3 Class 3K3 standard  
-5 °C up to +50 °C;  
max. 85% humidity or 25g/m3

Outdoor temperature range (BS in the external casing):  
in accordance with IEC721-3-3 Class 4K2 standard  
-20 °C up to +50 °C;  
max. humidity 85%

## External casing for base station

- Dimensions (L x W x D in mm): 296 x 256 x 90
- Weight: 960g





# Our strengths - Your advantages

Siemens is known worldwide as a trailblazer in the advancement of information and communication technologies. No other company offers such a comprehensive and innovative product portfolio.

With Siemens' unique HiPath Convergence Architecture, customers can migrate securely and flexibly into the world of innovative IP convergence solutions innovativer IP convergence solutions.

[www.siemens.com/hipath](http://www.siemens.com/hipath)

© Siemens AG 2004 • Information and Communication Networks • Hofmannstr. 51 • D-81359 Munich

**Reference No.: A31002-M2000-A130-5-7629**

The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract. Printed in the Federal Republic of Germany.